



Hovedspesifikasjon

Produktbeskrivelse:	Acer PD 527W - DLP-projektor
Enhetstype:	DLP-projektor
Innebygde enheter:	Høytaler
Dimensjoner (BxDxH):	28.3 cm x 25.6 cm x 10.4 cm
Vekt:	2.7 kg
Bildets lysstyrke:	3000 ANSI-lumen
Kontrastforhold:	2000:1
Oppløsning:	1024 x 768
Naturlig sideforhold:	4:3
Fargestøtte:	24-bit (16,7 millioner farger)
Lampetype:	P-VIP 230 watt
Lampens Levetid:	2000 time(r) / 4000 time(r) (sparemodus)
Videoinngang:	RGB, S-Video, kompositt video, komponentvideo (PAL-B/G, PAL-N, PAL-M, PAL-I, NTSC 4.43, NTSC 3.58, PAL-D, SECAM L, PAL-H, SECAM K1, SECAM D/K, SECAM B/G), IEEE 802.11g-trådløs
Digital videostandard:	Digital Visual Interface (DVI), High-Definition Multimedia Interface (HDMI)
Digitalfjernsynsvideoformater:	480p, 720p, 1080i, 480i, 576i, 576p
Videoutgang:	RGB
Lydutgang:	Høytaler(e) - integrert
Lydmodus:	Mono 3 watt
Inn-enhet:	Fjernkontroll
Strømforsyning:	AC 120/230 V (50/60 Hz)
Strømforbruk ved drift:	322 watt
Fabrikantgaranti:	2 års garanti

Utvidetspesifikasjon

Generelt	
Bredde:	28.3 cm
Dybde:	25.6 cm
Høyde:	10.4 cm
Vekt:	2.7 kg
Enhetstype:	DLP-projektor
Innebygde enheter:	Høytaler
Diverse	
Tilleggsutstyr inkludert:	Bæreveske, linsehette
Kabler inkludert:	1 x VGA-kabel 1 x komposittkabel 1 x S-Video-kabel 1 x HDTV-adapter 1 x strømkabel 1 x USB-kabel 1 x lyd kabel - fra 3,5 mm til 3,5 mm
Strømforsyning	

Strøminnretning:	Strømforsyning - intern
Påkrevd nettspenning:	AC 120/230 V (50/60 Hz)
Strømforbruk ved drift:	322 watt
Fabrikantgaranti	
Service og støtte:	2 års garanti
Service- og støttedetaljer:	Begrenset garanti - deler og arbeid - 2 år - innbringning Begrenset garanti - lampe - 90 dager
Miljøparametere	
Lydutslipp:	32 dBA
Videoinngang	
Analogt Videosignal:	RGB, S-Video, kompositt video, komponentvideo
Analogvideoformat:	PAL-B/G, PAL-N, PAL-M, PAL-I, NTSC 4.43, NTSC 3.58, PAL-D, SECAM L, PAL-H, SECAM K1, SECAM D/K, SECAM B/G
Digital videostandard:	Digital Visual Interface (DVI), High-Definition Multimedia Interface (HDMI)
LAN og Wireless Image Transferring Protocols:	IEEE 802.11b, IEEE 802.11g
Digitalfjernsynsvideoformater:	480p, 720p, 1080i, 480i, 576i, 576p
Inn-enhet	
Type:	Fjernkontroll - ekstern - trådløs
Bevegelsesdeteksjonsteknologi:	Laser
Lydutgang	
Type:	Høytaler(e) - integrert
Lydmodus:	Mono
Utgangskraft / kanal:	3 watt
Høytaler(e):	1 x blandet kanal
Projektor / Panel	
Maks synk-hastighet (V x H):	85 Hz x 100 kHz
Fargestøtte:	24-bit (16,7 millioner farger)
Bildets lysstyrke:	3000 ANSI-lumen
Kontrastforhold:	2000:1
Bildestørrelse:	0.64 m - 7.62 m
Lampetype:	P-VIP 230 watt
Projeksjonsavstand:	1.2 m - 12.02 m
Oppløsning:	1024 x 768 (innebygget) / 1280 x 1024 (komprimert)
Bildeklarhet (redusert):	2400 ANSI-lumen
Lampens Levetid:	2000 time(r) / 4000 time(r) (sparemodus)
Naturlig sideforhold:	4:3 Native 16:9 Compatible
Videoutgang	
Analogt Videosignal:	RGB
Ekspansjon / Tilkoplinger	
Grensesnitt:	1 x USB - 4 pin USB Type B 1 x DVI-I-inngang - 29-pin kombinert DVI 1 x VGA-inndata - 15-pin HD D-Sub (HD-15) 1 x seriell RS-232 (behandling) 1 x lydinngang - minijack 3,5 mm 1 x komponentvideoinngang - RCA 1 x S-video-inngang - 4 PIN mini-DIN 1 x VGA-utdata - 15-pin HD D-Sub (HD-15) 1 x nettverk - RJ-45 1 x lydutgang - minijack 3,5 mm 1 x kompositt videoinngang - RCA
Projektorlinsesystem	
Loddrett trapeskorleksjon:	-16 / +16
Keystone-korreksjonsretning:	Vertikal



Behringer B2030A

Aktiv 2 veis studio monitor. Ultra-lineær frekvens respons fra 50Hz til 21kHz. Innebygget forsterker på 75 og 35 watt. Ferrofluid-kjølt diskant tweeter. 6 3/4" bass. Magnetisk skjernet.

The TRUTH B2030A has all of the great features of an active TRUTH monitor packed in a compact cabinet! It's a high-resolution, active 2-way reference studio monitor that is perfect for nearfield monitoring applications: from small mixing environments to multi-channel surround setups.

Despite its small size, the TRUTH B2030A can achieve a **peak** output level in excess of 113 dB SPL. Powered by separate 75- and 35-Watt built-in amplifiers with an active crossover, these monitors provide ultra-linear **frequency** response from 50 Hz to 21 kHz.

A long-throw 6 3/4" woofer with a special polypropylene diaphragm delivers smooth, deep bass, while an extremely high-resolution HF driver delivers highs that are crystal-clear and full of detail. The unique BEHRINGER wave guide and the extremely low-distortion **crossover** network produce an absolutely linear phase response with excellent sound dispersion and stereo imaging.

The B2030A is equipped with servo **balanced** inputs on **XLR** and 1/4" TRS connectors to handle a variety of audio sources. Thanks to its compact size and magnetic shielding, the TRUTH B2130A can be placed near video monitors, computer displays or **digital audio** workstations. The B2030As are delivered along with individual measurement diagrams.



Kenwood DVD-spiller

DVF-3300-S DivX, Xvid, Pal progressive, Slim (DVF-3300-S)

Features

- [
- * Single DVD Video Player
- * Progressive Scan (K type)
- * PAL Progressive Scan (E, X type)
- * DivX Video Playback
- * MP3 / WMA Playback
- * DVD-R/RW, DVD+R/RW, CD-R/RW Playback
- * JPEG Playback
- * S-VCD Playback
- * On screen display
- * Program play
- * Random play
- * Repeat play
- * A-B Repeat play
- * Slow / Fast motion playback
- * Freeze frame and frame advance/back
- * 1 x Composite video output
- * Component Video out (Y, Cb, Cr Video output)
- * Scart Plug Connector (for E type)
- * Coaxial Digital output

Audio Specifications	<ul style="list-style-type: none"> * D/A Conversion * Oversampling 8 fs * Oversampling 4 fs * Frequency response <ul style="list-style-type: none"> Sampling frequency 44,1kHz Sampling frequency 48 kHz Sampling frequency 96 kHz * Signal to noise ratio * Dynamic range * Total harmonic distortion: * Channel separation * Wow and flutter * Analog output level/impedance * Digital output level/impedance 	<ul style="list-style-type: none"> 96kHz, 24 bit DAC 44,1 - 48 kHz 96 kHz 8 Hz ~ 20 kHz 8 Hz ~ 22 kHz 8 Hz ~ 44 kHz More then 100 dB More than 92 dB Less than 0.008 % (1 kHz) More than 95 dB (1 kHz) Below measurable limit 2 V / 330 Ω (COAXIAL): 0.5 Vp-p / 75 Ω
Video Specifications	<ul style="list-style-type: none"> * Video output format: * DVD Video compression: * Composite video output level: * Component Video output level <ul style="list-style-type: none"> Y-signal Cb-signa Cr-signal * RGB output level (SCART) : Horizontal resolution Video signal to noise ratio 	<ul style="list-style-type: none"> NTSC/PAL MPEG-2 1 Vp-p (75 Ω load, sync. negative) 1 Vp-p (75 Ω) 0,7 Vp-p (75 Ω) 0,7 Vp-p (75 Ω) 0,7 Vp-p (75 Ω) More than 500 lines More than 68 dB
General	<ul style="list-style-type: none"> * Power Consumption * Dimensions (WxHxD) * Weight 	<ul style="list-style-type: none"> 8W 440mm x 41mm x 249mm 1,9 kg